

HiPo6 Series - PAR38



Features

- High Power 6 (HiPo6) bulb - Brighter than ever before. Improved cooling, performance
- Perfect replacement for metal halides and halogens
- 6 Circle lenses allow for more LED chips placement for higher brightness
- Embedded cooling fan technology to ensure long life and decrease rate of decay of LEDs
- 15°, 25°, 45°, 80° beam angles
- Custom CCT possible
- For track fixtures, recessed housing or other indoor/dry applications*

Applications

- Retail stores (Jewelry, Clothing, Bags, Electronics, etc)
- Showrooms
- Galleries
- Museums
- Commercial Buildings (lobbies, high ceiling areas)
- Trade shows

SPECIFICATIONS

Power:	60 W
Input Voltage:	AC 100-240V 50-60Hz
Light Source:	36 pcs of High Power OSRAM LEDS (CREE - 24 pcs LEDS)
CCT:	3000K, 6000K, 7500K
Lumens:	4800-5300 lm
CRI:	>80
Beam Angle:	15°, 25°, 45°, 80°
Dimensions:	120 Ø x 137 H (mm) / 4.72 Ø x 5.39 H (inches)
Life Time:	50,000 hrs
Certifications:	UL, CE, FCC, RoHS
Operating Temp:	-4° ~ 104° (F) / -20° ~ + 40° (C)
Usage:	Indoor/dry location
Socket Base:	E26
Dimmable:	No
Type:	PAR38
Shell Color:	White
Warranty:	2 Years limited warranty

Ordering Guide:

PAR38-HiPo6-_____ - _____

CCT	Beam Angle
3000K	15°
6000K	25°
7500K	45°
	80°

Example: PAR38-HiPo6-7500K-45°

Notes

* Do not install in airtight environment. Air circulation is required for the cooling fan technology to properly.